

 Refer to warnings and safety information on pages 3-4 and page 83

Boston Washdown 1000®



Tube: Nitrile
Reinforcement: Wire, 1 Braid
Cover: Vinyl Nitrile
Color: Yellow (YW), Grey (GR)
Temperature Range: -40°F to +180°F
Type Of Branding: Ink Print
Working Pressure: 1,000 PSI
Type Of Coupling: 'M' Series, 'U' Series, 430 'U' Series or Interlocking. Clamps—Interlocking.

Features:

- Vinyl nitrile cover
- Nitrile tube
- Continuous permanent brand
- Longer lengths

Advantages:

- Abrasion, animal fat, vegetable oil, and weather resistant
- Heat resistant
- Detergent resistant
- Easy identification
- Economical; less waste

Markets:

- Food Industry
- Poultry Processing
- Industrial Cleaning Markets
- Construction Industry

Applications:

- Washdown of food processing facilities and equipment
- Transfer of hot detergent type solutions for cleaning equipment, tanks, buildings, etc.; maximum temperature of +180°F
- Convey air and water

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	MTO* MIN. ORDER QTY.	STANDARD COILS (FT)
H061006-350R	3/8	9.5	1	11/16	17.5	25	1,000	5	—	350(YW)
H061008-350R	1/2	12.7	1	27/32	21.4	32	1,000	7	—	350(YW)
H061012-350R	3/4	19.1	1	1-5/32	29.4	46	1,000	9-1/2	—	350(YW)
H062706-350R	3/8	9.5	1	11/16	17.5	25	1,000	5	4,800	350(GR)
H062708-350R	1/2	12.7	1	27/32	21.4	32	1,000	7	3,600	350(GR)

Reels will vary from 300 to 400 feet with maximum of 3 pieces per reel, no piece less than 50 feet.

*MTO - Made to Order