

 Refer to warnings and safety information on pages 3-4 and page 66.

### Boston Wildcat Hot Air



**Tube:** EPDM

**Reinforcement:** Fiber, 4 Spiral or 2 Ply and Helical Wire

**Cover:** EPDM/Pinpricked

**Color:** Brown

**Temperature Range:** +300°F

**Type Of Branding:** Printed Strip

**Suction:** Full Vacuum

**Working Pressure:** 100-150 PSI (Depending on coupling)

**Type Of Coupling:** Cam and Groove, or Combination Nipple. Clamps—Band.

#### Features:

- EPDM cover
- EPDM tube
- Continuous printed brand/brown color
- Longer lengths
- Pin pricked

#### Advantages:

- Abrasion, heat and weather resistant
- Heat resistant (intermittent service to 350°F)
- Easy identification
- Economical; less waste
- Hot air permeation

#### Markets:

- Tank Trucks
- In-plant Transfer
- Construction

#### Applications:

- Hot air blower hose; hot, dry, non-oily air applications

PRODUCT NUMBER	NOMINAL I.D.		REIN	O.D.		APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MINIMUM BEND RADIUS		STANDARD LENGTH
	(IN.)	(MM)		(IN.)	(MM)			(IN.)	(MM)	
H034948-100	3	76.2	4 Sp	3-47/64	94.9	230	150	9	228.6	100
H034964	4	101.6	2 Ply	4-39/64	117.1	290	100	11	279.4	50
H034964-100										100
H034964-150										150

*Heat resistant (intermittent service to 350°F).*