

 Refer to warnings and safety information on pages 3-4 and page 63

**Boston Washdown 1000®**



**Tube:** Nitrile  
**Reinforcement:** Wire, 1 Braid  
**Cover:** Vinyl Nitrile  
**Color:** Yellow (YW), Grey (GR)  
**Temperature Range:** -40°F to +180°F  
**Type Of Branding:** Ink Print  
**Working Pressure:** 1,000 PSI  
**Type Of Coupling:** 'M' Series, 'U' Series, 430 'U' Series or Interlocking. Clamps—Interlocking.

**Features:**

- Vinyl nitrile cover
- Nitrile tube
- Continuous permanent brand
- Longer lengths

**Advantages:**

- Abrasion, animal fat, vegetable oil, and weather resistant
- Heat resistant
- Detergent resistant
- Easy identification
- Economical; less waste

**Markets:**

- Food Industry
- Poultry Processing
- Industrial Cleaning Markets
- Construction Industry

**Applications:**

- Washdown of food processing facilities and equipment
- Transfer of hot detergent type solutions for cleaning equipment, tanks, buildings, etc.; maximum temperature of +180°F
- Convey air and water

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	MTO* MIN. ORDER QTY.	STANDARD COILS (FT)
H961006-350R	3/8	9.5	1	11/16	17.5	25	1,000	5	—	350(YW)
H961008-350R	1/2	12.7	1	27/32	21.4	32	1,000	7	—	350(YW)
H961012-350R	3/4	19.1	1	1-5/32	29.4	46	1,000	9-1/2	—	350(YW)
H962706-350R	3/8	9.5	1	11/16	17.5	25	1,000	5	4,800	350(GR)
H962708-350R	1/2	12.7	1	27/32	21.4	32	1,000	7	3,600	350(GR)

*Reels will vary from 300 to 400 feet with maximum of 3 pieces per reel, no piece less than 50 feet.*

\*MTO - Made to Order